



LUN HYPER 5

↓ 71g ↓ 2w

Compared to Hyper3

Compared to Hyper3 at 48km/h

Stronger. Stiffer. Unyielding.

Hyper 5 rims are built with new carbon fiber layer design-boasting a 377 GPa elastic modulus vs. 230 GPa in Hyper3.
Less flex, more control. No matter the speed, no matter the load, the rim holds its line. Always.



New hidden spoke design

The hidden spoke nipples reduce aerodynamic drag by creating a cleaner rim profile, minimizing turbulence at high speeds and enhancing overall airflow efficiency-engineered for every watt to count.



Lightweight hub design

HYPER5 hubset is 59g lighter-Gen 3: 357g/pair; Gen 5: 298g/pair.
With equivalent overall stiffness, the HYPER5 wheelset is lighter.
Modular system in the hub makes maintenance easier.





Glossy Black/White Decal



UD Matt/Laser Decal



Matt Black/White Decal

Model	D40	D50	D60
Rim Appearance	Glossy Black White Decal	UD Matt Laser Decal	Matt Black White Decal
Brake	Disc-Brake		
Rim Material	T700+M40		
Weight	1195g	1263g	1350g
Rim Height	40/40mm	50/50mm	60/60mm
Internal Rim Width	23mm		
External Rim Width	30.5mm		
Spoke Material	Carbon Fiber		
Spokes	Front wheel: 21PCS Rear Wheel: 21PCS		
Spoke lacing method	Front Wheel: 2:1, Rear Wheel: 2:1		
Bearings	Ceramic Bearing		
Hub Structure	Titanium Ratchet (36T)		
Free Hub	Shimano/XDR/CP/N3W		
Tire size	25-40mm		
Compatible Tire	Tubeless/Clincher		
Max. Tire Pressure	120psi		

